WEBCAMS

Easycam USB 2.0 VGA 1.3M

Introduction

Clamp the Typhoon EasyCam USB2.0 VGA 1.3M on the Notebook or desktop, it allows you to use in most areas. The 350K pixel CMOS sensor provides sufficient quality for most web uses and chat applications.
Capture video in near 30 frames per second, and at resolutions up to 1024 x 480.

Features

- CMOS Sensor; 350K pixel Hardware, 1300K pixel software support
- Approximately 30 frames/second full screen image at 1024 x 768 resolution, with no mosaic image. No delay image in general light conditions.
- USB2.0 interface, quicker speed and clearer imagine.
- USB2.0 Maximum transmission speed up to 480Mbps
- Internal image compression engine, maximum 2-7 times.
- Auto-exposure control
- Auto-plus control
- Auto B/W balance adjustment
- Super digital image control function, i.e. Color saturation, contrast, gamma sheet adapt outside and door security.

Specifications

- Maximum Resolution: 1280 × 960 (VGA)
- Imagine Resolution: 640 × 480 (VGA) 30 frames/second
- Imagine Sensor: 1/4 CMOS VGA sensor
- Lens: 6mm
- Lux: 0.8
- Focus: 30mm ~ infinity
- Color: 24bit.CCIR656
- S/N: > 42dB
- USB2.0 interface
- Supports DirectX
- Operating voltage: DC5V
- Currency: 65mA
- TWAIN Driver: Support all kinds of video chatting, video 0conference software.
- VFW Interface: Support capture dynamic and static imagine Direct Show: Support long distance dynamic immediate transmission.

System Requirements

- Intel® Pentium® III or above
- 128MB of System RAM
- USB2.0 port
- Windows® 2000 / XP operating systems or later
- Over 20MB of free hard disk space

EAN: 40 19337 50946 5

Art. no. 50946